

PCB

Power Connection Box

FEATURES

- For interfacing between a motor power supply and the
- Output connections: single-phase or three-phase
- Current rating: 55 A Voltage rating: 600 V
- Wire gage: 8–12 AWG or 12–18 AWG Conduit available in custom lengths

DESCRIPTION

The PCB Power Connection Box is a simple interface connection for powering a motor under test. One end is attached to a (customer-supplied) power supply and the other end is attached, via lead wires, to a test motor.

PCB-3 Three-phase Power Connection Box

ORDERING INFORMATION

MODEL NUMBER:	PCB
OUTPUT CONNECTION • Single-phase (1Ø) • Three-phase (3Ø)	A B
WIRE GAGE • 12 – 18 AWG ———— • 8 – 12 AWG	1 2
CONDUIT LENGTH • Specify length in (whole) mete	rs — — X

Example:

A PCB-B-2-3 is a three-phase power connection box with 8 – 12 AWG wire gage and 3 meters of conduit.

DIMENSIONS

	in	mm
length	8.625	219
width	4.700	119
height	2.310	59

NOTE: Dimensions are of box only and do not include power terminals.

Detailed dimension drawings can be found on Magtrol's web site. Solid 3D models are also available by contacting Magtrol Customer Service.

Due to the continual development of our products, we reserve the right to modify specifications without forewarning.



MAGTROL INC

70 Gardenville Parkway Buffalo, New York 14224 USA Phone: +1 716 668 5555

Fax: +1 716 668 8705 E-mail: magtrol@magtrol.com

MAGTROL SA

Centre technologique Montena 1728 Rossens/Fribourg, Switzerland Phone: +41 (0)26 407 3000 Fax: +41 (0)26 407 3001

E-mail: magtrol@magtrol.ch

www.magtrol.com

- Subsidiaries in:
- Germany
- France
- Great Britain China

Worldwide Network of Sales Agents

